

IN THE CLAIMS:

AD 1. (Currently Amended) A method of choosing an optimal candidate value to be used for matching a block from a first image (10) with an area from a second image (11), the method comprising: (a) making a set of candidate values for determining an area to be matched from the second image (11), (b) for each candidate value from the set, determining an area to be matched from the second image (11), based on said candidate value, matching the block from the first image (10) with this area and calculating a matching error, and (c) choosing the optimal candidate value from the set based on the calculated matching errors, characterized in that the block is formed by pixels, a selection is made of pixels of the block from the first image which are visible in the area to be matched from the second image (11), and the calculation of a matching error excludes from the calculation said pixels of the block that are not selected in said selection~~is based on said selection.~~

2. (Original) A method as claimed in claim 1, characterized in that the selection is made by determining for the pixels of the block from the first image (10) what their location is in the area to be matched from the second image (11), and selecting a pixel based on a comparison with other pixels of the block from the first image (10) which are found at the same position in the area to be matched from the second image (11).

3. (Currently Amended) A method as claimed in claim 2, ~~characterized in that~~ wherein said comparison is made based on depth of the pixels to be compared. in

their respective images.

AD
CAL

4. (Currently Amended) A system for choosing an optimal candidate value to be used for matching a block from a first image with an area from a second image, the system comprising: a collector (43), which is arranged for making a set (45) of candidate values (20, 21, 22, 23) for determining an area to be matched from the second image, a matcher (46), which is arranged for determining for each candidate value from the set based on said candidate value an area to be matched from the second image, matching the block from the first image with this area and calculating a matching errorarea, and a selector (47), which is arranged for choosing the optimal candidate value from the set (45) based on the calculated matching errors (24), characterized in that the block is formed by pixels, and the matcher (46) is arranged for making a selection of pixels of the block from the first image, which are visible in the area to be matched from the second image, and the matcher (46) is arranged for calculating a matching error, said pixels of the block that are not selected in said selection being excluded from the calculation~~based on said selection.~~

5. (Original) A system as claimed in claim 4, characterized in that the matcher (46) is arranged for making the selection by determining for the pixels of the block from the first image what position they have in the area to be matched from the second image, and selecting a pixel based on a comparison with other pixels of the block from the first image which have the same position in the area to be matched from the second image.

6. (Currently Amended) A system as claimed in claim 4, ~~characterized in that~~
the wherein said comparison is made based on depth, of the pixels to be compared, in
their respective images.

AD
CD-1
7. (Original) An apparatus for processing a video signal (40) that consists of a
variety of images, comprising: a system (43, 46, 47) as claimed in claim 4, 5 or 6, for
choosing an optimal candidate value (48) to be used for matching a block from a first
image with an area from a second image (40), the system being arranged for choosing
optimal candidate values for blocks from the images from said variety, and an image
processor (41) for processing the video signal (40) to obtain an enhanced video signal
based on the obtained optimal candidate values as determined by said system (43, 46,
47).

8. (Original) An apparatus as claimed in claim 7, characterized in that the
apparatus further includes a display system (42) for displaying the enhanced video signal.

9. (New) A method of choosing an optimal candidate value to be used for
matching a block from a first image (10) with an area from a second image (11), the
method comprising: (a) making a set of candidate values for determining an area to be
matched from the second image (11), (b) for each candidate value from the set,
determining an area to be matched from the second image (11), based on said candidate
value, matching the block from the first image (10) with this area and calculating a

AD
CDL +

matching error, and (c) choosing the optimal candidate value from the set based on the calculated matching errors, characterized in that the block is formed by pixels, a selection is made of pixels of the block from the first image which are visible in the area to be matched from the second image (11), and the calculation of a matching error is based on said selection, characterized in that the selection is made by determining for the pixels of the block from the first image (10) what their location is in the area to be matched from the second image (11), and selecting a pixel based on a comparison with other pixels of the block from the first image (10) which are found at the same position in the area to be matched from the second image (11).
